

In the Claims:

Claims 1-14, 19 and 20 are pending. Claims 15-18 are withdrawn. Please amend claims 1, 2, 10, 14 and 19 as follows:

1. (Currently Amended) A method for simulating an electric power network having a plurality of transmission-level buses and connected electrical elements and a plurality of distribution-level buses and connected electrical elements, the method comprising:

determining a model of the transmission-level buses and connected electrical elements, the model of the transmission-level buses including a plurality of transmission lines and a plurality of transmission electrical elements;

determining a model of the distribution-level buses and connected electrical elements, the model of the distribution-level buses including a plurality of distribution lines and a plurality of distribution electrical elements;

generating a single mathematical model by integrating the model of the transmission-level buses with the model of the distribution-level buses, wherein the single mathematical model further models the interdependency of the plurality of transmission lines and the plurality

of transmission electrical elements included in the model of the  
transmission level buses and the plurality of distribution lines and the  
plurality of distribution electrical elements included in the model of  
the distribution-level buses;

simulating an operation of the electric power network with the single  
mathematical model; and

~~generating~~ outputting data describing the simulated electric power network.

2. (Currently Amended) A method for analyzing an electric power network having  
a plurality of transmission-level buses and connected electrical elements and a  
plurality of distribution-level buses and connected electrical elements, the method  
comprising:

determining a model of the transmission-level buses and connected electrical  
elements, the model of the transmission-level buses including a  
plurality of transmission lines and a plurality of transmission electrical  
elements;

determining a model of the distribution-level buses and connected electrical  
elements, the model of the distribution-level buses including a  
plurality of distribution lines and a plurality of distribution electrical  
elements;

generating a single mathematical model by integrating the model of the transmission-level buses with the model of the distribution-level buses, wherein the single mathematical model further models the interdependency of the plurality of transmission lines and the plurality of transmission electrical elements included in the model of the transmission level buses and the plurality of distribution lines and the plurality of distribution electrical elements included in the model of the distribution-level buses;

assessing under load flow analysis at least one of a condition and a performance of the simulated electric power network; and

~~generating~~ outputting data describing at least one of the condition and the performance of the simulated electric power network.

3. (Original) The method of claim 2, further comprising:

integrating models of theoretical distribution-level real and reactive energy sources connected to one or more of the plurality of distribution-level buses into the single mathematical model; and

observing impacts and effects across the simulated electric power network of the theoretical distribution-level real and reactive energy sources connected on one or more of the plurality of distribution-level buses.

4. (Original) The method of claim 2, further comprising:

integrating models of theoretical alternative topologies of the distribution-level portions of the electrical power network into the single mathematical model; and

observing impacts and effects across the simulated electrical power network of the alternative topologies of distribution-level portions of the network.

5. (Original) The method of claim 2, further comprising:

integrating additional models of theoretical distribution-level loads into the single mathematical model; and

observing impacts and effects of load growth across the simulated electrical power network due to the addition of theoretical distribution-level loads.

6. (Original) The method of claim 2, further comprising:

integrating models of theoretical transmission-level real and reactive energy sources connected to one or more of the plurality of transmission-level buses into the single mathematical model; and

observing impacts and effects across the simulated electric power network of  
the theoretical transmission-level real and reactive energy sources  
connected on one or more of the plurality of transmission-level buses.

7. (Original) The method of claim 2, further comprising:

integrating models of theoretical alternative topologies of the transmission-  
level portions of the electrical power network into the single  
mathematical model; and

observing impacts and effects across the simulated electrical power network  
of the alternative topologies of transmission-level portions of the  
network.

8. (Original) The method of claim 2, further comprising:

integrating additional models of theoretical transmission-level loads into the  
single mathematical model; and

observing impacts and effects of load growth across the simulated electrical  
power network due to the addition of theoretical transmission-level  
loads.

9. (Original) The method of claim 2, wherein the integrating models further  
comprises:

representing actual distribution-level buses and elements having an actual voltage and an actual topology with corresponding models of buses and elements characterized, at least in part, by representations of the actual voltages and the actual topologies of the distribution-level buses and elements.

10. (Currently Amended) A method for analyzing performance of a modeled electric power network having a plurality of transmission-level buses and connected electrical elements and a plurality of distribution-level buses and connected electrical elements, the method comprising:

determining a model of the transmission-level buses and connected electrical elements, the model of the transmission level buses including a plurality of transmission lines and a plurality of transmission electrical elements;

determining a model of the distribution-level buses and connected electrical elements, the model of the distribution level buses including a plurality of distribution lines and a plurality of distribution electrical elements;

generating a single mathematical model by integrating the model of the transmission-level buses with the model of the distribution-level

buses, wherein the single mathematical model further models the interdependency of the plurality of transmission lines and the plurality of transmission electrical elements included in the model of the transmission level buses and the plurality of distribution lines and the plurality of distribution electrical elements included in the model of the distribution-level buses;

assessing by load flow analysis a condition and a performance of the modeled electric power network;

adding incremental real and reactive energy sources in locations of the modeled electric power network;

assessing by load-flow analysis the condition and performance of the simulated electric power network with the added incremental real and reactive energy sources;

determining whether the performance of the modeled electric power network is improved as a result of the added real and reactive energy sources;

determining a set of added real and reactive energy sources that yields a greatest improvement in network performance;

characterizing the set of added real and reactive energy sources as specific distributed energy resources; and

~~generating~~ outputting data describing the set of added real and reactive energy resources.

11. (Original) The method of claim 10, further comprising, quantifying an improvement in performance of the modeled electric power network due to the set of added real and reactive energy sources.

12. (Currently Amended) The method of claim 10, wherein adding incremental real and reactive energy sources further comprises:

representing the energy sources with models of the energy sources

characterized, at least in part, by values of corresponding electric power network actual bus location and actual voltage level;

adding to the single mathematical model the models of the energy sources at one of the distribution-level buses and transmission-level buses, wherein the models of real energy sources are added subject to actual limits appropriate for dispatchable demand reductions available on the electric power network, and the real energy sources with reactive energy sources are added subject to actual limits appropriate for generation at load sites within the electric power network.



13. (Original) The method of claim 10, wherein determining whether the performance of the modeled electric network is improved as a result of the addition of energy sources comprises:

considering selected characteristics of a reduction of real power losses and reactive power losses, improvement in voltage profile, improvement in voltage stability, improvement of load-serving capability, and avoidance of additions of electric elements connected to the network that would otherwise be required.

14. (Previously Presented) The method of claim 10, wherein characterizing the additions of real and reactive energy sources comprises:

creating a plurality of mathematical models each having both distribution-level buses and connected electrical elements and transmission-level buses and connected electrical elements under a plurality of network operating conditions;

determining the additions of models of real and reactive energy sources that achieve the greatest improvement in network performance of the modeled network under each set of operating conditions;

characterizing each incremental addition of real or reactive energy sources as  
a discrete generation project, dispatchable demand response project,  
or capacitor bank project; and  
comparing results achieved under each set of operating conditions to derive  
model profiles for operation of each discrete added energy source  
model under each different set of operating conditions.

15. (Withdrawn) A method for analyzing an electric power transmission and  
distribution network for assessing impacts and benefits of distributed energy  
resources (DER) for the electric power transmission and distribution network, to  
provide indication of the extent to which the transmission-level resources and  
distribution-level resources impact on each other, and of the merits of remedying  
deficiencies near their network locations, the method comprising:

simulating the electric power transmission and distribution network with a  
mathematical model as an Energynet in which transmission voltage-  
level elements and distribution voltage-level elements are integrated  
within the mathematical model; and

incorporating models of distributed energy resources at a plurality of  
network locations and voltage levels within the simulated network for  
analyzing resultant effects.

16. (Withdrawn) A method for assessing impacts and benefits of distributed energy resources (DER) for an electric power transmission and distribution network, the method comprising:

adding models for real energy sources, reactive energy sources, and combined real and reactive energy sources to modeled network locations in selected combinations; and  
evaluating alternative combinations of the additions for their ability to improve selected characteristics of network stability, or voltage security, or reduction of real and reactive power losses, or deferral of conventional network modifications.

17. (Withdrawn) A method for assessing the potential impacts and benefits of distributed energy resources (DER) for an electric power transmission and distribution network, comprising:

adding to a network model a set of models of real and reactive energy sources for resultant improvement in network performance, independent of other considerations;  
characterizing the set of added energy sources as a performance portfolio of individual projects for distributed energy resources, including

dispatchable demand reduction, capacitive elements, and power generation; and

evaluating the economic value of improvements in network performance derived from proposed projects based on their similarity to the projects in the performance portfolio.

18. (Withdrawn) The method of claim 17, further comprising:  
identifying the proposed projects that most closely resemble projects in the  
performance portfolio; and  
selectively implementing the identified proposed projects for their beneficial  
economic or environmental impact and their beneficial performance  
improvement.
19. (Currently Amended) A computer readable medium comprising a computer  
program that when executed in a computer processor implements the steps of:  
determining a model of the transmission-level buses and connected electrical  
elements, the model of the transmission-level buses including a  
plurality of transmission lines and a plurality of transmission electrical  
elements;  
determining a model of the distribution-level buses and connected electrical  
elements, the model of the distribution-level buses including a  
plurality of distribution lines and a plurality of distribution electrical  
elements;  
generating a single mathematical model by integrating the model of the  
transmission-level buses with the model of the distribution-level  
buses, wherein the single mathematical model further models the  
interdependency of the plurality of transmission lines and the plurality

of transmission electrical elements included in the model of the  
transmission level buses and the plurality of distribution lines and the  
plurality of distribution electrical elements included in the model of  
the distribution-level buses;

integrating models of the distribution-level buses and connected electrical  
elements with models of the transmission-level buses and connected  
electrical elements into a single mathematical model;

simulating an operation of the electric power network with the single  
mathematical model;

calculating at least one of a condition and a performance of the simulated  
electric power network; and

~~generating~~ outputting data describing at least one of a condition and a  
performance of the simulated electric power network.

20. (Original) The computer readable medium of claim 19, further comprising a  
computer program that when executed in a computer processor further implements  
the steps of:

integrating models of theoretical distribution-level sources of real and  
reactive energy sources connected to one or more of the plurality of  
distribution-level buses into the single mathematical model; and

calculating impacts and effects across the simulated electric power network  
of the theoretical distribution-level real and reactive energy sources  
connected on one or more the plurality of distribution-level buses.